



Rain proof slim type REPSN SEIRES

RPS-400HL-12 / RPS-300HL-12/RPS-200HL-12/RPS-100HL-12



























sn.com APPLICATION

- » Industrial automation control;
- » LED lighting, industrial control equipment, power equipment;
- » Semiconductor refrigeration and heating;
- » Liquid crystal display;
- » Audio and video products, security monitoring

FEATURES

- » Universal AC input range AC180V 240V;
- » Nylon plastic on both ends of the power supply, to prevent high temperature, anti freezing, prevent aging;
- Built-in heat sink, hydraulic fan, intelligent temperature dontro improve the effect of heat dissipation and prolong the service life of products;
- Adopts single FR-4 PCB, surface screen printing on the component side, solder joint surface use gold plating process;
- 100% full load aging test, to ensure that every product is safe and NNN. reliable, excellent quality.

PARAMETERS

RPS-400HL-12	RPS-300HL-12	RPS-200HL-12	RPS-100HL-12
L238*W50*H24	L208*W50*H24	L180*W50*H24	L140*W50*H24
AC187-262V	AC187-262V	AC187-262V	AC187-262V
DC12V	DC12V	DC12V	DC12V
33.3 A	25 A	16.7 A	8.3 A
400W	300W	200W	100W
≥20000h	≥20000h	≥20000h	≥20000h
-25~+60℃ 10%	~90%RH		
lp64	lp64	lp64	lp64
	L238*W50*H24 AC187-262V DC12V 33.3 A 400W ≥20000h -25~+60°C 10%	L238*W50*H24 L208*W50*H24 AC187-262V AC187-262V DC12V DC12V 33.3 A 25 A 400W 300W ≥20000h ≥20000h -25~+60℃ 10%~90%RH	L238*W50*H24 L208*W50*H24 L180*W50*H24 AC187-262V AC187-262V AC187-262V DC12V DC12V DC12V 33.3 A 25 A 16.7 A 400W 300W 200W ≥20000h ≥20000h ≥20000h -25~+60 °C 10%~90%RH

ATTENTION




The power supply is made of metal aluminum shell, and has been treated with colored oxidation. The shell has been grounded. It should be grounded reliably during installation to ensure safety. Do not connect either the live wire or the neutral wire to the ground wire to prevent fire. w.repsn.com

- » Do not installed the product place where is easily immersed;
- » Do not install the power near flammable and explosive goods;
- » Install the power supply in a well-ventilated place;
- » When the power supply installed in the outdoor, must be installed in vertical suspension way;


DIMENSION


RPS-400HL-12













RPS-300HL-12



RPS-100HL-12



PACKING



SUZHOU REPSN PHOTOELECTRIC TECHNOLOGY CO.,LTD.

Add: NO.999 Xingdong Rd Wangshan industrial park Wuzhong district.Suzhou city.China

Tel: +86-0512 -66536260

Http://www.repsn.com Mail: led@repsn.com